

SAMBA 75
GSM/GPRS/EDGE

Internet Mobility at Work



Internet Mobility at Play



FALCOM
WIRELESS COMMUNICATIONS GMBH

The FALCOM SAMBA 75

is a Plug-and-Play, compact, light-weight, wireless modem that provides EDGE, GPRS and GSM connectivity for portable handheld computers and others. The major benefit over earlier SAMBA GSM/GPRS modem is that SAMBA75 supports EDGE and additionally offers a TCP/IP stack.

SAMBA75 allows subscribers to send and receive data, including images, web pages and photographs, with a transfer rate three times higher than possible with GSM/GPRS services. It supports MMS, SMS & fax.

It can be easily controlled by using AT command for all kinds of operations.

The SAMBA75 is designed for use on any GSM network in the world.

Quad Band GSM/GPRS/EDGE Modem

- Integrated Quad Band GSM/GPRS/EDGE engine
- GSM 850/900/1800/1900 MHz
- Data, Fax, SMS, MMS
- Audio/Video streaming
- Integrated SIM interface
- GSM antenna included
- Plug-n-Play
- Integrated USB-Hub
- Very lightweight
- World-wide applicable



Technical Specification

<p>General</p> <ul style="list-style-type: none"> • Quad-band GSM/GPRS/EDGE modem 850/900/1800/1900 MHz • Class 4 (2W) for EGSM450 • Class 1 (1W) for DCS1800/PCS 1900 • Small size and low power consumption • Fax/data transmission without extra hardware • Internal 3 V SIM interface • Easy remote control by AT commands for dedicated applications • Fully type approved according to GSM phase 2 + specification • Fully shielded and ready-to-use 	<p>Basic features</p> <ul style="list-style-type: none"> • SMS (GSM and GPRS mode): text and FDL, SMS, MMS point to point MT and MO, SMS broadcast • GSM circuit data features: transparent and non transparent up to 9600 bps, group 3, class 1, class 2 alternative fax, MHP 2
<p>Electrical characteristics</p> <ul style="list-style-type: none"> • Power supply: +5 VDC (through USB port) 	<p>GPRS packet data features</p> <ul style="list-style-type: none"> • data uplink transfer : max. 42.8 kbps; • data downlink transfer : max. 85.6 kbps; • coding schemes CS1 to CS4 • WAP-compliant and compliant with SMG-3!
<p>Physical characteristics</p> <ul style="list-style-type: none"> • Dimensions : (L x W x H) : 88.7mm x 57.6mm x 12.6mm • Weight : 7.9g • Normal range temperature : -20°C to +55°C • Restricted operation : -30°C to +20°C and +55°C to +60°C 	<p>EDGE features</p> <ul style="list-style-type: none"> • data transfer max. 384 kbps • provides audio/video streaming
<p>Interfaces</p> <ul style="list-style-type: none"> • Single antenna interface • Internal SIM interface: 3 V only • USB serial link 	<p>Other features</p> <ul style="list-style-type: none"> • SIM, network and service provider locks • Real time clock • UCS 2 character set management



CREATIVE CENTURY
MANAGEMENT SDN BHD (JEREMBAN)